



PROFESSIONAL SERIES OF DEHUMIDIFIERS SERIES: "T" AND "TE"

The most economical method of safe and convenient dehumidification
– naturally and fast.
Suitable for use in any ambient with high humidity.



CLPR
CERTIFICATION



EKOTEZ®

EKOTEZ Ltd.
Koněvova 47, 130 00 Prague 3
Czech Republic
Phone: +420 2258 2291, Fax: +420 22258 6265
e-mail: commerce@ekotez.cz
web: www.ekotez.cz

DEHUMIDIFICATION

Effective dehumidification is helpful.

PROFESSIONAL DEHUMIDIFIER SAVES YOUR MONEY

Applications:

- ✓ Drying out new buildings
- ✓ Drying out water damage
- ✓ Keeping storage rooms and warehouses, cellars dry
- ✓ Drying out any type of materials
- ✓ Drying equipment and vehicles used in commerce
- ✓ Dehumidifying for indoor pools
- ✓ Dehumidifying and drying out in areas of water works to avoid corrosion damage
- ... and many additional areas

Quick and safe dehumidification is required in many areas. Whether for drying out new buildings, drying out water or moisture damage or regular drying of materials. Effective dehumidification is important to avoid damage or to speed up further processing. Ekotez Professional series dehumidifiers have heavy-duty construction and design. They can be easily transported, are simple to operate and are ready for use immediately. You achieve the best dehumidification results because our units are highly effective and at the same time have low energy consumption.

Technical specifications

Type	T40 / TE40	T90 / TE90	T120 / TE120
Application area humidity	30% - 95% RH	30% - 95% RH	30% - 95% RH
Application area temperature	0°C - 35°C	0°C - 35°C	0°C - 35°C
Airflow	500 m ³ /h	1100 m ³ /h	1500 m ³ /h
Dehumidification output	40 L / 24h	90 L / 24h	120 L / 24h
Voltage	220 - 240 V / 50Hz	220 - 240 V / 50Hz	220 - 240 V / 50Hz
Power consumption + heating	650W + 1200W	1200W + 1200W	1400W + 1200W
Width x Depth x Height (mm)	495x830x610 mm	600x640x850 mm	600x640x1070 mm
Weight	36,5/37 kg	51/51,5 kg	60/60,5 kg

TE series have additional heating to achieve even better performance. Dehumidifier is produced in compliance with CE requirements. Certificate issued by the approved institutes



FEATURES:

- Safe and careful drying out
- Robust construction
- Simple operation
- Ready to plug in and operate immediately
- High operational reliability
- Highly effective and low on energy consumption
- Optimum output sizes due to a variety of models
- Handlers for easy transport + Wheels on larger units for easy transport and quick repositioning
- Electronic control
- Automatic defrosting
- Built-in hygrostat
- Refrigerant R410A



Distributor: